



Always wear appropriate eye protection!

- 1. Attach Item D (2) to the top hole in the front cowl on both sides of the cart as shown in Picture 1 using the supplied bolt.
- 2. Level bracket, drill and attach the bottom 2 holes as shown in Picture 2. We suggest using a washer or 2 as indicated in Picture 2 between the inner hole of the golf cart and upper brush guard plate.
- 3. Lift Item A approximately 1" of the rear body and drill holes 3/8" and mount the U-Bolts to the stock mounts or box/seat back brackets. This mounting plate is universal.

Pic 1



4. Mount Item B (2) to both sides of Item A using the supplied nuts and bolts.

5. Mount Item C (2) to both Item D and Item B as shown using the supplied nuts and bolts.

6. Securely tighten all nuts and bolts.


WARNING: This device does not provide roll-over protection.
NON-R.O.P.S.

**RATED** 





Pic 3



## **Indemnification And Insurance Agreement**

High Performance Enhancement Kit purchaser assumes sole and entire responsibility for, and shall indemnify and save harmless Nivel LLC, from any and all claim, liability, responsibility, and persons or property that may be sustained in connection with the use of any product before or after purchase, including but not limited to high performance enhancement lift kits. The High Performance Enhancement Kit purchaser also shall indemnify Nivel LLC harmless with respect to any and all liability that may be incurred.

Golf Cars are recommended for use only by those aged 16 and older. Golf Cars can be especially hazardous to operate. Always remember that riding and alcohol/drugs don't mix. Never ride on public roads. Never carry more than two passengers (except shuttles and trams). Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Nivel LLC reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models, or equipment without notice and without incurring any obligation.



