

REAR SEAT BAG RACK

INSTALLATION INSTRUCTIONS

STEP 1) MOUNT SUPPORT BARS ONTO BOTTOM OF BAG RACK AS SHOWN.

STEP 2) MOUNT BAG RACK ASSEMBLY ONTO SAFETY HANDLE:

REMOVE (4) WINGNUTS & HARDWARE. BEGIN TO LOCATE BAG RACK:

NOTE: LIFT UNIT UPWARD UNTIL SUPPORT BARS CONTACT UNDERSIDE OF FOOTREST. CLAMP IN PLACE FLUSH WITH SAFETY HANDLE. DRILL (4) HOLES USING PRE-DRILLED BAG RACK AS A GUIDE.

STEP 3) ASSEMBLE UNIT ONTO SAFETY HANDLE AND REMOVE CLAMPS.

SPECIAL NOTE:

WHEN STRAPING BAG ONTO RACK
PLACE STRAP THROUGH
BUCKLE ONLY ONCE.

STEP 2

BAG RACK UNIT MOUNTS HERE;
ONTO SAFETY HANDLE.

REQUIRES (4) 17/64" HOLES (STEP #2)

BAG RACK UNIT
(STRAPS NOT SHOWN)

STEP 3

UP

FOOTREST

STEP 1

SUPPORT BARS ARE SHOWN IN PLACE; *IMPORTANT*:
PAY ATTENTION TO SUPPORT BARS IN STEP 2:
RAISE BAG RACK UPWARD UNTIL SUPPORT BARS
ARE CONTACTING THE UNDERSIDE OF FOOTREST.

HARDWARE INCLUDED:

BAG RACK MAIN ASSEMBLY
LOWER BARS (2)
THUMB SCREWS & OTHER HARDWARE
(IN PLACE ON BAG RACK ASSEMBLY)

TOOLS REQUIRED:

17/64" DRILL BIT/DRILL
7/16" SOCKET
7/16" WRENCH
"C" CLAMPS